



Speedpro Imaging

MAGNETIC SIGN USAGE INSTRUCTIONS

INSTALLATION

- The surface area should be free of dust, dirt, grease or other contaminate.
- Ensure that the back side of the Magnetic is clean before applying to vehicle
- Ensure that no part of the vehicle surface contains Bondo or body filler.
- The Sign will not adhere to vehicle surfaces that are of non-ferrous composition (i.e. aluminum, fiberglass, high-density plastic, etc.)
- Do not cover body moldings, grooves, handles, windows or other extrusions
- Do not extend signs beyond the contours of the vehicle.
- Wait at least 90 days before installing on freshly painted vehicles
- Wait at least 60 days before installing on freshly clear coated vehicles
- Wait at least 3 days before installing on freshly waxed vehicles
- Avoid installing Magnetic Signs where there is a danger of gasoline spillage

REMOVAL

- Do not leave signs on the vehicle unattended. They may be stolen
- The Sign **must** be removed from the vehicle at least once a week
- Signs with dark background colours **must** be removed at least twice a week

CLEANING

- Clean with soapy water and a rag.
- Do not use chemicals, solvents or harsh cleaners
- Do not use a brush or other abrasive tools

STORAGE & CARE

- When storing lay them completely flat in a dry, warm place.
- Never bend or fold the sign as this may result in permanent damage. Bends or bubbles may allow air to lift the magnetic from the surface of the vehicle.
- If slight folds or creases occur by accident, lay the Sign down on a flat surface and soften with the heat from a blow dryer. Do not use a Heat Gun or Steam.

It is not possible for *Speedpro Signs* to offer any guarantees on lost, stolen, or damaged Magnetics. Following these guidelines will help extend the life of your Magnetic Sign

“Speedpro Imaging – It all Starts with an Idea...”

Speedpro Imaging 1200 Speers Road #23, Oakville ON
Tel: 905-582-4873 E-Mail: burloakcustomercare@speedpro.com