



VEHICLE GRAPHIC CARE SHEET

CLEANING

- Clean with Rag, Sponge or Soft Brush & mild soap and warm water
- For Tar & Grease use Mineral Spirits or IPA
- Do not use Hard Bristle Brushes
- Avoid Harsh Cleaning solutions
- Do not use Brush Type Car washes
- Avoid using Wax as some wax may cause the vinyl to crack

PRESSURE WASHING

- Pressure should not exceed 1300 PSI
- Temperature should not exceed 60 degrees Celsius (140 F)
- Nozzle 12 inches or more away from vehicle and at an angle no less than 60 degrees
- Do not pressure wash any Perforated Window Film

WINDOWS

- Do not use Rear Window Defogger if Graphics or Lettering are on Rear Window
- Do not use Rear Window Wiper if Graphics or Lettering are on Rear Window
- Do not Roll Down any Window that has Graphics or Lettering installed on it
- Do not use Ice Scrappers on any window that has Graphics or Lettering installed on it

OTHER CONCERNS

- Do Not Pick at the edges of the Graphic or Lettering
- Avoid prolonged exposure to Petroleum spillage
- Avoid Exposure to Harsh caustic or acidic chemicals

“Speedpro Imaging - Helping your Business Succeed!”

Speedpro Imaging 1200 Speers Road, #23, Oakville ON, L6L 2X4
Tel: 906-582-4873 E-Mail: burloakcustomercare@speedpro.com